

SO 2.0

SETTING SHEET Ver.01

CIRCUIT

- INDOOR OUTDOOR
- DIRT ASTROTURF CARPET GLASS WOOD
- WET DRY DUSTY SMOOTH BUMPY
- HARD PACKED CLAY BIUE GROOVE _____
- LOW TRACTION MED TRACTION HIGH TRACTION

DRIVER _____

DATE _____

FRONT

Z2-017GA (DTM3.1)
 Z2-017-3A (S01.0/2.0)

Plastic
 Aluminum

Wide Narrow
 Plastic
 Aluminum

Standard (Z2-008F3A)
 Graphite (Z2-008F3GA)

+1 ↑ Plastic
 0 ↑ Aluminum
 Steel

CAMBER ↔ _____ °

TOE IN OUT _____ °

RIDE HEIGHT _____ mm

Graphite Hard
 Wide Narrow

Wide (S02.0)
 Wide
 Narrow

SPRING

Dot _____

OIL

φ1.6x2/2.0

_____ mm x _____

_____ mm x _____

REAR

CAMBER ↔ _____ °

RIDE HEIGHT _____ mm

Plastic
 Aluminum

L5 Standard Graphite
 S3 Z2-415RS2A (Aluminum)

Plastic
 Z2-415RS2A (Aluminum)

S M L

0.5
 1
 1.5

Standard (S01.0/2.0)
 High mount (DTM3.1)

0.05 0.1 0.5 1

SPRING

Dot _____

OIL

φ1.7x2/2.0

_____ mm x _____

_____ mm x _____

DRIVE

OLD LCL
 03 02 01 00

4-gear 2-gear
 # _____

MOTOR ⇨ _____ Rotor _____ mm

GEAR ⇨ Spur T / Pinion T : 2.6

BATTERY ⇨ _____

ESC ⇨ _____

SETTING ⇨ _____

Main chassis

S02.0
 S01.0
 DTM3.1
 CAL3.1

Steel
 Aluminum

YT-RWS10A x _____
 YT-RW25A x _____

Steel
 Aluminum
 Plastic
 Carbon

TIRE

FRONT

TIRE ⇨ _____

INSERTS ⇨ _____

WHEELS ⇨ _____

REAR

TIRE ⇨ _____

INSERTS ⇨ _____

WHEELS ⇨ _____

OTHER

Z2-DTM31 WA (Aero Hi-clearance 7')
 Z2-CAL2WA (LMR27)

COMMENT